

RICH COAT

INTERIOR

RICH COAT Interior Emulsion is a durable premium water based, 100% acrylic emulsion.

FEATURES AND BENEFITS:

- Rich and Smooth Finish
- Durable Abrasion Resistant
- Vertical and Overhead Applications
- Excellent Washability
- Fungal and Mildew Resistant
- Weather Resistant Finish
- Stain Resistant
- Above Grade Decorative Finish
- Ready to Use

USES:

As a Finish Coat Over

Concrete – prestressed, plastered, POP, stucco and putty finishes.

PREPARATION:

Clean area remove all unsound material, grease, oil, paint and any other foreign materials that will inhibit performance. Remove excess surface water and puddles prior to use.

For interior walls, ceiling ensure proper leveling of surface by applying FineCoat Wall Putty and Primer.

PLACEMENT:

It is advisable to apply two even coats of all of the Rich coat materials to insure maximum coverage of the substrate and performance of the system.

Spray Application

The following information is offered as a guide only. Specific product, equipment, application conditions and user experience will influence proper equipment selection. Consult with the equipment handling

techniques. Field Test material with equipment prior to starting project.

Pump	Hose Dia. & Max length	Gun	Tip	Pressure at Pump	Pressure at Gun
2 gal min. 3000psi	3/8"x150	Airless	0.026" 0.031"	2800 psi	2200 psi

Brush or Roll Application

Rich Coat should be applied in two even coats to provide a total wet film thickness of 6-10 mils (150 – 250 microns). Use a synthetic 3/4" nap roller or brush.

CURING

Rich coat dries and cures through the evaporation of water and coalescing to form a film. Drying will be dramatically extended in cool damp weather. Supplemental indirect heat will be necessary at or below 10°C to insure proper curing. Depending on temperature, humidity and wind conditions, Rich coat dries within 3-5 hours.

TECHNICAL DATA:

- Abrasion Resistance - 1700 cycles at 100micron.
- Freeze-Thaw Resistance- Passes 3 cycles
- Alkali Resistance - Passes no blistering
- Gloss - 2 – 8@ 60deg GH
- Stability of the thinned Paint - 24 hours
- Flash Point - N.A.
- % Solids - 48 – 53 %
- Pigment Volume Conc. - 46%

COVERAGE:

On normal masonry surface by brushing

1st coat : 125 – 150 sq ft./ltr

2nd coat : 150 - 175 sq ft./ltr

Coverage may vary considerably depending on the substrate conditions (rough or smooth), finishing technique used, and the final thickness of the coating.

PACKAGING:

Available Pack sizes - 20 ltr, 200 ltr

COLOURS:

Rich Coat is available in White and all existing standard shades. **Rich Coat** standard shades are manufactured from the finest color pigments and tinters available.

SHELF LIFE:

One year from date of manufacture.

LIMITATIONS:

- **Do Not** allow to freeze.
- **Do Not** apply over substrates that are frozen or contain frost.
- **Do Not** use Rich coat on horizontal substrates, roofs, swimming pools or where standing water is likely to occur.
- **Do Not** apply when atmosphere or substrate temperature is below 10°C or above 40°C.
- **Do Not** apply when humidity is below 10% or above 80%.
- **Do Not** add or mix any materials with the coating unless approved by the **Conpro Enterprises Pvt. Ltd.**
- **Do Not** store below 10°C or above 40°C.
- **Do Not** entrap air while mixing.
- **Do Not** apply when substrates containing pyrite(iron sulphide)
- **Do Not** use over epoxy, urethane or high gloss surfaces.

- **Do Not** apply if rain is forecast within 24 hours.
- **Do Not** apply over concrete cured less than 28 days.

CAUTION: Contains Acrylic Emulsion, Glycol and preservatives. Irritant. Avoid contact with eyes or prolonged contact with skin. In case of contact, flush thoroughly with water. For eyes, flush thoroughly with clean water for at least 15 minutes and get prompt medical attention. Do not inhale. In case of inhalation move to fresh air and seek medical attention. Empty container may be hazardous to children. **KEEP OUT OF REACH OF CHILDREN.**

LIMITED WARRANTY: Conpro Enterprises Pvt. Ltd warrants that this product and the materials used therein meet or exceed the applicable standards listed and enforced at the time of manufacture. Company will replace any product or part, which proves defective due to quality of ingredients used or due to the manufacturing process itself. This warranty shall apply only if the product is used in strict accordance to applicable specifications and instructions provided by Conpro Enterprises Pvt. Ltd for its use, and company shall not be liable otherwise. Replacement of any defective product, or, Conpro Enterprises Pvt. Ltd option, refund of the purchase of any defective product shall be the be the buyer's sole remedy under this Warranty, and the company shall in no event be liable for any damages in excess of the purchase price of the defective product **CONPRO ENTERPRISES PVT. LTD SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL OR SPECIAL DAMAGES.**

CONPRO ENTERPRISES PRIVATE LIMITED

S.No.: 271/3A-3D, Asliamman Koil Street,
Venbedu, Thiruporur – 603110. Ph: 9500104295

Email : sales@supercem.in